













NUPPO ENGINEERING SYNDICATE (P) LTD.

GATE VALVE

API 600 | API 6D

Material of Construction:

CI|CS|SS|AS|WCB|LCB| WC6 | WC9

End Connections:

Screwed to BSP|BSPT|NPT| Socket Weld | Butt Weld Ends | Flanged Ends | Ring Type Joints (RTJ)

Pressure Rating:

ASA 125# | 150# | 300# | 400# | 600# | 900#

Operation:

Manual | Gear and Electrical Actuator

Size Range: 25mm to 1200mm



SLUICE VALVE

IS 14846

Material of Construction:

CI | CS | GM | DI

Flanged Ends

Pressure Rating:

Rating: PN 0.6 | PN 1.0 | PN 1.6 | PN 2.0

Inside Screw (Non Rising Spindle) for Sluice | Outside Screw

(Rising Spindle) for Gate

Size Range:

25mm to 1500mm



BUTTERFLY VALVE

API 609 | BS-5155 | BS EN 593 | AWWA C504 | IS 13095

Material of Construction:

CI | DI | CS | SS

Seat & Seals:

Nitrile | Neoprene | PTFE | Viton |

Hypalon | Silicon

End Connections: Wafer Type | Double Flanged | Lug End

Pressure Rating:

ASA 125# | 150# | PN 1.0 | PN 1.6 |

PN 2.0 | PN 2.5

Type:

Centric Disc Design | Offset Disc Design |

Triple Offset Disc Design | High Performance

Operation:

Lever | Gear | Electrical Actuator | Pneumatic Rotary Actuator

Size Range:

40mm to 2000mm



End Connections:

PN 2.5 | PN 3.0 | PN 3.5 | PN 4.0

NON RETURN VALVE

Material of Construction:

CI | CS | SS | AS | LCB | WC6 | WC9

Size Range:

15mm to 1000mm

SWING TYPE

BS 1868 | IS 5312

Flanged End | Buttweld End

Pressure Rating:

125# | 150# | 300# | 600# | 900# |

PN 10, 16, 20, 25, 40

WAFER CHECK VALVE

API 6D

Wafer Type

Pressure Rating:

PN 10 | PN 16



NON SLAM DISC CHECK VALVE

BS 7438

Wafer Type

Pressure Rating:

PN 10 | PN 16 | PN 40



Flanged End | Wafer Type

Pressure Rating:

Size Range:

25mm to 1800mm



DUAL PLATE CHECK VALVE

API 594

PN 10 | PN 16 | PN 25 | PN 40





IS 14845

Material of Construction:

CI | CS | GM | DI

End Connections: Screwed | Flanged End

Single Acting | Double Acting |

Kinetic Type Isolating

Pressure Rating:

ASA 125# | 150# | 300# | PN 1.6 PN 2.0 | PN 2.5 | PN 3.0 | PN 3.5 | PN 4.0

Size Range:



Nupro engineering syndicate (P) LTD.

GLOBE VALVE

BS-1873 | ND-16 | ND-40

Material of Construction:

CI | CS | SS | AS | LCB | WC6 | WC9

End Connections:

Screwed to BSP|BSPT|NPT| Socket Weld|Butt Weld Ends| Flanged Ends|Ring Type Joints (RTJ)

Pressure Rating:

ASA 125# | 150# | 300# | 600# | 900# | 1500# | 2500# | PN 16 | PN 40 | PN 64

Operation:

Manual | Gear and Electrical Actuated

Size Range:
15mm to 300mm



KNIFE EDGE GATE VALVE | PULP VALVE

Material of Construction:

Body: CI | CS | SS

End Connections:

Flanged End | Wafer Lugg Type

Type:

UNI-DIRECTIONAL | BI-DIRECTIONAL

Operation:

Handwheel | Gear | Pneumatic Cylinder

Pressure Rating:

PN 10 | PN 16

Size Range:

50mm to 1200mm



PLUG VALVE

BS-5158 | BS-5353

Material of Construction:

CI | DI | CS | SS

Type:

PTFE Sleeved | Lubricated

Non-Lubricated

End Connections:

Screwed | Flanged | Buttweld

Pressure Rating:

Class 150#

Size Range:

25mm to 200mm



SAFETY VALVE

API 526

Material of Construction:

CS | SS

End Connections:

Flanged End

Type:

Ordinary Lift Type | High Lift Type |

Full Lift Type

Pressure Rating:

ASA 150# | 300# | PN 40 Size Range :

25mm to 200mm



STRAINER

Material of Construction:

CI | CS | SS

End Connections:

Flanged | Screwed End

Type:

"Y" Type | "T" Type | Pot Type | Basket Type

Pressure Rating:

ASA 150# | 300# | PN 40

Size Range:

15mm to 200mm



DIAPHRAGM VALVE

BS-5156 | BS-6755-1

Material of Construction:

CI | CS | SS

Lining Options:

Rubber Lined | Glass Lined | Unlined

End Connections:

Screwed | Flanged End

Pressure Rating:

PN 10 | PN 16 | 150# Class

Size Range:

25mm to 400mm



SLUICE GATE

IS 3042 | IS 13349

Material of Construction:

CIIDIISSIMS

Type:

Open Channel Type | Wall Mounted Type |

Timble Mounted Type

Operation:

Manual I Gear I Electrical Actuator

Size Range:

200mm to 2000mm

(Other any size on request)



Manufacturer of all types of Industrial Valves, Pipe & Pipe Fittings, Sluice Gate in India.

NUPPO ENGINEERING SYNDICATE (P) LTD.

BALL VALVE - FLOATING & TRUNION MOUNTED

BRONZE VALVE

BS-5351 | BS-5159

Material of Construction:

CI | CS | SS | AS | A 105 | F3.4 | F316 CF3 | CF3M | CN7M

Seat & Seals:

PTFE | Reinforced PTFE | Buna-N |

Graphoil | Graphite

End Connections:

Screwed to BSPT | NPT | Socket Weld | Butt Weld with extended Nipple I Flanged Ends I Butt Weld Ends

Pressure Rating:

ASA 150# | 300# | 600# | 800# |

Single Pc I Two Pc I Three Pc I 3 Way I 4 Way

Operation:

Lever | Gear | Electrical Actuator |

 Gate Valve as per IS 778 CL-I Globe Valve as per IS 778 CL-I

· Horizontal Non Return Valve

Pneumatic Rotary Actuator

Size Range:

GUN METAL

as per IS 778 CI-I

· Steam Stop Valve

6mm to 200mm

FORGED STEEL VALVE - GATE, GLOBE CHECK "T" - TYPE STRAINERS

API 602 | BS-5352

Material of Construction:

ASTM A 105 | F304 | F304L | F316 | F316L | F5 | F9 | F11 | F22

End Connections:

Socketweld | Screwed | Butt Weld | Flanged End

Type:

Straight Pattern I "Y' Type Pattern

Pressure Rating:

ASA 150# | 300# | 600# | 800# | 1500# | 2500#

Size Range:

15mm to 50mm



FLANGES & FITTINGS

Material of Construction:

CIIDIIMSIA105 I

SS 304 | SS 316 | SS 304L | SS 316L

Rating:

ASA 150# TO 2500# I ND-16 I ND-40 I BS 10 TABLE E | D | F | K | J

Type:

SORF | Blind | WNRF Etc.

Size Range:

15mm to 1200mm



* The Design & Technical Data Furnished Here Are Subject to Change Without Intimation Due to Continuous Product Development.

TPI AGENCY












NUPTO ENGINEERING SYNDICATE (P) LTD.

Manufacturer of all types of Industrial Valves, Pipe & Pipe Fittings, Sluice Gate in India.

CIN: U29120WB1975PTC030200



- m +91 98300 07152 / 98743 52605
- nuprovalve@yahoo.co.in
- www.nuprovalve.com



